Instructions Elivi PRO USB-C Docking 9 in 1 Model number: ELV-USBCDK-9 Package Contents USB C Hub x 1 User Manual x 1 www.elivi.no	Thank you for purchasing our 9 in 1 USB-C Multiport Hub. Please read this user manual carefully and keep it in a safe place for future reference. System Requirements: This product is a Plug and Play product. Laptop with an available USB-C Port Windows 7/8/10, MacOSX v10.0 or above operating systems, USB 3.0/3.1/3.2/Thunderbolt 3/4.	① USB-C Male ② USB2.0 TYPE-A 480Mbps ③ USB2.0 TYPE-A 480Mbps ④ USB2.2 GEN2 TYPE-C 10G ⑤ USB3.2 GEN2 TYPE-A 10G ⑥ USB-C PD ④ HDMI2.0 4K@60HZ ④ HDMI2.0 4K@60HZ ④ USB3.2 GEN2 TYPE-A 10G ⑤ Ethernet RJ45 1000Mbps	HDMI supports 4Kx2K/60Hz, downward compatible with 4k@30hz/1080P/1080I/720P Two HDMI simultaneously display output support HDMI2.0b.* *Note: To use the simultaneously display via 2HDMI ports, the host of USB-C source port must be DP 1.4, the hub takes DP 1.4 multi-stream input. 3Ports 10Gbps. 2Ports USB TYPE-A 3.2 Gen2 10Gbps data transmission, 1Port TYPE-C 10Gbps 3.2 Gen2.	2 Ports USB2.0 TYPE-A 480Mbps. Ethernet Gigabit Ports. RJ45 standard with the flip structure design, makes the whole HUB Ultra-slim USB-C Charging port supports PD3.0, supports 100W power in, power out(charging) is limited to 87W for safety.
Plug the USB-C male connector of the Hub into the USB-C port on your USB-C laptop. USB-C Power Delivery: Charge your laptop by plugging the USB-C Charger to the Multiport Hub USB-C Female Power Delivery (PD) port. HDMI Outputs: Connect to your Data Monitor, UHDTV or projector with an HDMI 2.0 cable via the HDMI output port and start working, watch videos from your USB-C laptop on your Monitor, TV or other HDMI-enabled devices.	USB Ports: We recommend you use the 2x USB-A/1x USB-C 10Gbps ports for Web Camera, Hard Drives, data transfer and other speed demanding USB-peripherals. 2 x USB-A 2.0 Ports we recommend you use for keyboard, mouse, headset, wireless USB dongles and other USB 2.0 USB peripherals. RJ45 Ethernet: Connect to your network via RJ45 Ethernet cable.	Notes The up to 100W charging speed can only be achieved when used with a 100W rated USB-C PD cable in combination of 100W type-C PD Power Adapter. For more stable connection when using high-power devices, connect a PD Power Adaptor to the USB-C female PD port. The USB-C female PD port of this product is only for charging USB-C laptops whose USB-C Port supports USB Power Delivery(PD). The PD USB-C female port of this product does not support data transfer.	The USB-C female data port of this product is only for data transfer. The USB-C female data port of this product does not support charging. HDMI 1.4 cables only support 30Hz, HDMI 2.0 cables support 4K up to 60Hz. You can also use HDMI 2.1 cables. 4K 60Hz Compatibility requires a DP 1.4 compatible type-C port on your device. (Please look at details under "Main features 1".) Temperature of USB-C Hub can be high when all ports and charging of laptop is used, this is normal. Temperature will be lower after charging is completed.	If you need any assistance, please contact our support team with your product model number and order number. Imported and distributed by: CBK Distribusjon AS Gneisveien 30 2020 Skedsmokorset Norway www.cbk.no +47 22903700